



PRODUCT DATA SHEET

MULTIFLEET Diesel Engine Oil

15W40 CG-4/SJ

Code:140

MULTIFLEET is a high performance, low ash, detergent type diesel oil designed for use in turbo charged and naturally aspirated diesel engines.

SPECIFICATIONS

MULTIFLEET meets or exceeds the following specifications

- API CG-4/SJ
- VOLVO VDS-2
- MACK EO-L, MACK EO-L PLUS
- SAE 15W40
- ALLISON TYPE C4
- DAIMLER BENZ DB 229. 1, 228.1
- ACEA E2, B2/A2
- CUMMINS CES 20071, 20076
- MAN 271

APPLICATIONS

MULTIFLEET is a superior diesel engine oil particularly suited for use in mixed fleet applications, primarily diesel engines manufactured prior to 1998.

MULTIFLEET will offer increased protection, easy cranking in cold weather, reduced emissions and minimise oil burning, if present.

MULTIFLEET is NOT suited for diesel engines fitted with electronic injection or Exhaust Gas Recycling (E.G.R.).

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	15W40
Specific gravity at 15C	0.887
Viscosity at 40C, mm ² /s (cSt)	110
Viscosity at 100 C, mm ² /s (cSt)	15
Viscosity index	130
TBN mgKOH/g	8.04
Sulphated ash, %	1.03
Flash point C	220

PACKAGE SIZE 1, 5, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.