



PRODUCT DATA SHEET

DETROIT DD 40 Diesel Engine Oil

SAE 40 CF-2/SG

Code:160

DETROIT DD 40 is a monograde SAE 40 diesel oil and falls into the category of a superior performance "Series 2" diesel engine oil.

SPECIFICATIONS

DETROIT DD 40 meets or exceeds the following specifications.

- API CF-2/SG
- GENERAL MOTORS - DETROIT DIESEL
- SAE 40
- BULLETIN 7SE270 (Revised 9185)
- US MILITARY MIL-46152C, 2104D

APPLICATIONS

DETROIT DD 40 is a low ash lubricant which ensures minimal crown land piston deposits and prevents top ring carbon build up. This product has been specifically formulated to suit the requirement of providing excellent valve train wear protection and minimise the likelihood of engine cylinders becoming "glazed" under less severe operating conditions.

DETROIT DD 40 is suitable for use in Detroit Diesel 2- Cycle engines, series 53, 71 & 92 as well as other equipment running under severe load conditions.

DETROIT DD 40 may also be used for other brands of diesel engines which are experiencing oil loss or poor compression.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	SAE 40
Specific gravity at 15 c	0.887
Viscosity at 40c, mm ² /s (cSt)	165
Viscosity 100c, mm ² /s (cSt)	16
Viscosity index	100
TBN, mgKOH/g	6
Flash Point C	210
Sulphated ash %	0.95

PACKAGE SIZE 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.