



PRODUCT DATA SHEET

MULTI-SYN

Semi-Synthetic Automotive Engine Oil

15W40 SM/CF

Code:202

MULTI-SYN is a semi-synthetic oil which provides better protection from piston deposits, less oil thickening, sludge deposits and exceptional anti-wear protection under high speed and high stress.

SPECIFICATIONS

MULTI-SYN meets or exceeds the following specifications.

- API SM/CF
- ACEA A3/B3/B4
- DAIMLER BENZ DB 229.1
- SAE 15W40
- VW 500.00 / 505.00

APPLICATIONS

MULTI-SYN is suitable for all late model petrol engine vehicles requiring a 15W40 oil including those fitted with turbochargers. It is also ideal for use in L.P.G. fuelled vehicles and diesel engines where an API CF performance level is stipulated.

MULTI-SYN will provide superior defence from piston deposits, acid corrosion, oil consumption and sludge deposits. In addition using **MULTI-SYN** will offer your engine exceptional anti-wear protection when under high speed, high stress motoring conditions.

MULTI-SYN meets or exceeds the requirements of an SM/CF engine oil and will assist in maintaining engine cleanliness in all engines using both leaded and unleaded fuels. It will additionally assist in energy conservation and enhance fuel economy.

MULTI-SYN has a high viscosity index and ensures quick circulation of oil to all moving parts during cold weather starts, providing additional wear protection during this critical time of an engines operation.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	10W40
Specific gravity at 15 C	0.87
Viscosity at 40 C, mm ² /s (cSt)	105
Viscosity at 100 C, mm ² /s (cSt)	15
Viscosity index	140
TBN, mgKOH/g	8.9
Flash Point C	227

PACKAGE SIZE 5, 20 & 205 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.