PRODUCT DATA SHEET

DIESEL KNOCK OUT

Stop It Additive

Code:721

DIESEL KNOCK OUT is a high specification diesel fuel enhancer which will dramatically reduce vibration and noise in most diesel motors.

SPECIFICATIONS

DIESEL KNOCK OUT meets or exceeds the following specifications.

- ASTM D613

APPLICATIONS

DIESEL KNOCK OUT enhances the properties of the diesel fuel to provide quick and complete combustion. This delivers greater engine efficiency and noise and knock reduction up to 50%.

DIESEL KNOCK OUT will also provide increased useable power or fuel economy.

DIESEL KNOCK OUT offers smoother idle and easier cold starts

DIESEL KNOCK OUT extends oil life, reduces exhausted emissions, keeps injectors clean and prolongs engine life.

350 Mil bottle will treat up to 350 litres of diesel fuel.

MUST BE ADDED TO FUEL TANK BEFORE REFUELLING.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	
Specific Gravity	0.96 Kg/L
Viscosity @ 40 C cSt	2 Typical
Flash Point deg C	74 typical
Pour Point deg C	-45 typical
Max Long Term Storage Temp deg C	45
Sulphur content	Less than 15 ppm

PACKAGE SIZE	350 Mil & 4 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.